AGX™ Series

LED Grow Light - Full Cycle Cannabis Cultivation



The Evio AGX Series is a full-cycle top-lighting solution for commercial cannabis cultivation, with variable light intensities to use from vegetative growth to bloom.

APPLICATIONS

Indoor commercial cannabis cultivation












Performance Data

Catalog No.	Input Power	PPF (Nominal)	PPE (Nominal)	HID Replacement	Max. Amps. per Voltage			
					120V	208V	240V	277V
AGX-6L-320-850-IFC	320W	850 µmol/s	2.66 µmol/J	630W MH	2.67A	1.54A	1.33A	1.16A
AGX-6L-630-1700-IFC	630W	1700 μmol/s	2.70 µmol/J	1000W HPS	5.25A	3.03A	2.63A	2.27A
AGX-6L-630X-1900-IFC	630W	1900 μmol/s	3.02 µmol/J	1000W HPS	5.25A	3.03A	2.63A	2.27A

Spectrum Distribution



Ordering Information

Example: AGX-6L-320-850-IFC


AGX	6L	320	850	IFC	[Blank]	[Blank]	
Series AGX LED Grow Light	Form Factor 6L 6-Bar	Rated Power 320 320W 630 630W 630X 630W	PPF 850 850 μmol/s 1700 1700 μmol/s 1900 1900 μmol/s	Spectrum IFC Indoor Full Cycle	Input Voltage Blank 120V-277V	Cord / Plug Blank 8.5' Cord with 240V NEMA 6-15P Plug	



Performance Summary

AC Input Voltage	120V-277V
AC Input Power	320W, 630W
Light Source	LED
Spectrum	Indoor Full-Cycle
Nominal Beam Angle	120 Deg.
Mounting Height	6"-15" Above Canopy
Coverage	1 fixture per 4' x 4' area
Dimming	0-10V Continuous (10-100%)
Operating Temp.	-40°C to 50°C
THD	< 20%
Life Rating	75,000 hours
Certifications	ETL, DLC Hort.
Warranty	5 Years
Ingress Protection	Wet Location

Product **Dimensions**




PPFD Distribution - 12" Height from Canopy

_	-		_	_	_		_	_	_			
	Model No.: AGX-6L-320-850-IFC											
24"	351				352				353			
18"		465			439			472				
12"			572		564		579					
6"				622	617	616						
0"	603	592	617	623	624	627	625	603	617			
6"				595	599	611						
12"			555		557		557					
18"		457			420			462				
24"	351				351				355			
	24"	18"	12"	6"	0"	6"	12"	18"	24"			

	Model No.: AGX-6L-630-1700-IFC										
24"	649				690				648		
18"		884			841			880			
12"			1066		1089		1084				
6"				1194	1189	1195					
0"	1145	1143	1117	1205	1223	1221	1115	1140	1148		
6"				1189	1186	1188					
12"			1074		1016		1071				
18"		871			765			882			
24"	638				636				636		
	24"	18"	12"	6"	0"	6"	12"	18"	24"		

	Model No.: AGX-6L-630X-1900-IFC											
24"	716				736				718			
18"		938			950			935				
12"			1184		1195		1184					
6"				1347	1355	1349						
0"	1297	1281	1327	1361	1407	1371	1333	1284	1298			
6"				1344	1346	1342						
12"			1174		1194		1181					
18"		926			884			925				
24"	706				724				704			
	24"	18"	12"	6"	0"	6"	12"	18"	24"			



© 2022 Evio an Aleo Lighting, Inc. brand. All rights reserved. For informational purposes only. Reproduction in whole or part is prohibited without prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequences of its use. Aleo Lighting reserves the rights make changes in specification at any time without notice.

Evio an Aleo Lighting, Inc. brand www.eviogrow.com 10988 Bloomfield Ave. Santa Fe Springs, CA 90670 Ph: 877-358-8825

